



Technical Specification.

AFT flexi-dropper™, YB28 Series 28mm Braided, flexible sprinkler hose fitting:

MODEL	Nominal Length (mm)	Nominal inlet by outlet size (mm)	Equivalent length of Schedule 40 (DN25) pipe (meters)	Max num of 90deg bends	Min bend radius (mm)
YB28-700	700	25 x 15	3.05	2	76
		25 x 20	4.88		
YB28-1000	1000	25 x 15	4.88	2	76
		25 x 20	7.01		
YB28-1200	1200	25 x 15	6.10	2	76
		25 x 20	7.62		
YB28-1500	1500	25 x 15	7.01	2	76
		25 x 20	8.53		
YB28-1800	1800	25 x 15	9.75	3	76
		25 x 20	11.58		

AFT flexi-dropper™ YB25 Series 25mm Braided, flexible sprinkler hose fitting:

MODEL	Nominal Length (mm)	Nominal inlet by outlet size (mm)	Equivalent length of Schedule 40 (DN25) pipe (meters)	Max num of 90deg bends	Min bend radius (mm)
YB25-700	700	25 x 15	6.71	2	76
		25 x 20	8.53		
YB25-1000	1000	25 x 15	11.89	3	76
		25 x 20	16.47		
YB25-1200	1200	25 x 15	17.08	3	76
		25 x 20	19.21		
YB25-1500	1500	25 x 15	17.98	3	76
		25 x 20	22.57		
YB25-1800	1800	25 x 15	20.43	3	76
		25 x 20	22.57		



SILVER MEMBER
Fire Protection Association Australia